



PIDILITE INDUSTRIES LIMITED

Marketing Division: P.B. No. 17411, Andheri (East), Mumbai 400 059 (India).
Phone +91-22-28367085, Fax: +91-22-28357853, website: www.pidilite.com

TECHNICAL DATA SHEET

UNITINT

FOR INFORMATION ONLY

PRODUCT DESCRIPTION

Color Concentrate recommended for Enamels and water base Emulsion paints/Distempers.

TECHNICAL DETAILS

Composition : Pigmented colour concentrate.

Colour : Available in 17 popular shades.

Viscosity,

(BF-RVT, SPL.4RPM 20): 2 - 10 Ps

Tinting strength (std) : 97.0 to 103 %.

APPLICATION METHOD

Add Unitint gradually into base white/white or enamel white while stirring well. Shake Unitint bottle well before adding. Unitint should be added before thinning the base White /Acrylic Emulsion/Distemper/Enamel Paint.

ADVANTAGES

Very high tinting strength.

Good light fastness.

Easily intermiscible colors.

Economical.

PACKING

50, 100 & 200 ml plastic bottle.

STORAGE

Store in cool & dry shaded place, away from the sunlight.

SHELF LIFE

24 months from the production date when stored in the sealed original container.

HEALTH AND SAFETY INFORMATION

Please refer to MSDS

STATUS 01 - 06 - 2007

NOTE: -

We recommend that before using our product, the customer should make his own test to determine the suitability of the product for his own purpose under his operating conditions. As the circumstances under which our product is stored, handled & used, are beyond our control, we cannot assume any responsibility of their use by customer.
