



Crown Paints Kenya Ltd

Head Office
Likoni Road
PO Box 78848 - 00507
Nairobi, Kenya

Tel : +254 -20- 2165703/4/6
Or : +254 -20- 6533604-12
Fax : 6558480 / 6550712
www.crownpaints.co.ke

MATERIAL SAFETY DATA SHEET

1. Substance and Company Identification

Product Name: Crown Covermatt Emulsion,
Chemical Family: Water based Paint
Manufacturer: Crown Paints Kenya Limited, Mogadishu Road,
Industrial Area, Box 78848-00507, Nairobi, Tel:
+254-20-533603, Fax: +254-20-544641
Email: safety@crownpaints.co.ke; OR
shailesh.patel@crownpaints.co.ke; OR
sandile.shoko@crownpaints.co.ke.

2. Composition, Information and Ingredients

<u>Substance</u>	<u>Weight %</u>
PVA Emulsion	3 – 6
Pigments & Extenders	45 - 70
Water	10 - 30
Additives	0.5 - 5

3. Hazard Identification

No significant hazards. Ammonia (<1%) can cause choking when inhaled.

4. First aid measures

Skin contact: May cause mild irritation. Wipe off and wash thoroughly with soap and water.

Eye contact: May cause mild irritation and redness. Wash with running water for 15 minutes.

Inhalation: May cause irritation to respiratory tract. Remove to fresh air.

Ingestion: Give 1-2 glasses of water to conscious victim. Do not induce vomiting.



Crown Paints Kenya Ltd

Head Office
Likoni Road
PO Box 78848 - 00507
Nairobi, Kenya

Tel : +254 -20- 2165703/4/6
Or : +254 -20- 6533604-12
Fax : 6558480 / 6550712
www.crownpaints.co.ke

5. Fire fighting measures

This is a non-flammable liquid.

Suitable extinguishing media: Carbon dioxide (CO₂) or universal aqueous film forming foam

Flash point: >100°C

6. Accidental Release Measures

Personal: Provide ventilation. Remove sources of ignition

Environmental: Do not flush into surface water or sanitary sewer systems

Clean up: Soak with inert material (e.g., sand, silica gel, acid binder, sawdust) and place in clean, empty containers for disposal. Dispose in accordance with the regulations.

7. Handling and Storage

Handling: Vapour may collect on low areas. Avoid breathing mist when spray applying or dust when sanding.

Storage: Store at temperatures between 1 and 40°C in a dry place. Protect from extreme heat and exposure to direct sunlight. Keep container tightly closed.

8. Physical and Chemical Properties

Appearance	Viscous liquid of various colours
pH	8.5 - 10
Specific gravity	1.3 - 1.5
Viscosity	110 - 130 KU
% volatile	10 - 70
Odour	Mild

9. Chemical stability and reactivity

This product is stable and will not undergo hazardous reactions. Avoid storage and using in temperatures below 1 and above 40°C. When heated to decomposition it emits acrid smoke and irritating fumes.

10. Toxicological information

Product has no toxicity or carcinogenic effect on human beings.



Crown Paints Kenya Ltd

Head Office
Likoni Road
PO Box 78848 - 00507
Nairobi, Kenya

Tel : +254 -20- 2165703/4/6
Or : +254 -20- 6533604-12
Fax : 6558480 / 6550712
www.crownpaints.co.ke

11. Ecological information

Environmental toxicity: Product has no known adverse effect on the ecology. Do not allow large undiluted quantities directly into waterways.

12. Transport information

Not classified or regulated as a hazardous material according to transport regulations but precautions should be taken to avoid freezing during transportation.