

Crown GP Matt Finish Paint

PRODUCT DESCRIPTION

Type: An alkyd resin-based topcoat with a smooth matt finish, designed for interior and exterior surfaces.

Uses: Ideal for decorating interior surfaces. Can also be used on exterior steel and wooden structures.

Substrates: Suitably primed and undercoated, cement plaster, concrete, wood and steel.

Advantages: Excellent opacity. Attractive matt finish which helps hide surface imperfections.

Conditions during application; The temperature of the substrate should be minimum 10°C and at least 3°C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying. The moisture content in the substrate should not exceed 3% (by weight). The coating should not be exposed to oil, chemicals or mechanical stress until fully cured.

PRODUCT DATA:

Colour Range: Available in black only

Pack Sizes: 1 litre and 4 litres

Finish: Matt

Thinner & equipment cleaner: White Spirit

Dilution Ratio: Supplied ready for use for brush application. Where necessary and for spray application thin with up to 10% by volume Crown White Spirit. Avoid over-thinning as this will affect the opacity and increase settlement during application. Stir well before use.

Drying Times: Surface dry <4hrs & Hard dry <16hrs

APPLICATION DATA:

The product can be applied by: Brush, roller or airless spray

Spreading Capacity per coat: Depends on film thickness applied, type of texture, surface porosity, imperfections, temperature & wastage during painting

13– 15 m²/l when applied on a smooth surface.

Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.

TECHNICAL DATA SHEET



If you like it... Crown it!

DIRECTIONS FOR USE

Surface preparation & Paint System:

Surface	Preparation	Primer/	Topcoat
New Plaster	Remove loose particles. Moisture content < 3%	Crown Plus 3 Masonry or Alkali Resistant Primer diluted up to 10% with White Spirit	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Emulsion painted surface in sound condition	Sand and clean	Crown Universal Undercoat diluted up to 10% with White Spirit	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Oil based enamel painted surface in sound condition	Sand down and clean	None required if in good condition unless a drastic colour change is required.	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Loosely bound & lime-washed or distempered surfaces	Remove all flaking paint down to a firm base or original building	Crown Penetrating Primer with no dilution	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Wood & boards	Sand along the grain	Crown White/ Aluminium Wood Primer diluted up to 10% with White Spirit	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Mild Steel	Degrease with White Spirit or degreaser. Remove rust with rust remover. Rinse with cleanwater till water break free	Crown Zinc Phosphate Primer	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Galvanised Iron/ Stainless Steel	Weather for 6 months. Apply Mordant Solution or 1-pack Etch Primer	Crown Zinc Phosphate Primer	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit
Plastic & Fibreglass	Apply Mordant Solution or 1-pack Etch Primer	Crown Universal Undercoat diluted up to 10% with White Spirit	1 - 2 coats Crown Matt Finish Black diluted up to 10% by volume with White Spirit

Precautions:

1. Stir paint thoroughly before use and intermittently during use to avoid settling
2. Not recommended where chemical and solvent resistance are required
3. Avoid applying heavy coatings above 35µm DFT to prevent wrinkling
4. Avoid the use of cheap solvents as these may affect gloss or drying time

Availability: From Crown Depots in Nairobi, Kisumu, Mombasa, Meru, Nyeri, Eldoret, Arusha, Mwanza, Dar es Salaam, Kigali and through Crown Stockists.

TECHNICAL DATA SHEET



If you like it... Crown it!

Storage Conditions: Store under cool dry conditions away from direct sunlight, heat and extreme cold.

Disclaimer: The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Crown Paints Kenya PLC control. Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Crown Paints Kenya PLC reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference.



For additional health & safety information, please refer to our Material Safety Data Sheet (MSDS)