

Crown 2530 Stronghold Parquet Adhesive

PRODUCT DESCRIPTION

Type: A homopolymer based adhesive for parquet flooring.

Recommended use: Sticking wood-block and parquet floorings to absorbent floor screeds

Substrates: Wood-block and parquet tiles.

Advantages: High bonding power. Quick drying. Water based - environmentally friendly/easy clean up.

PRODUCT DATA:

Colour Range: White viscous liquid

Pack Sizes: ½ Kg, 1Kg, 4Kg, 20kg and 25Kg

Thinner & equipment cleaner: Water

Thinning: Supplied ready for use. DO NOT THIN

Drying Times: Hard Dry: 1-2 hours **Full Cure:** 4 hours

APPLICATION DATA:

The product can be applied by: Comb trowel

Spreading Capacity per coat: Depends on film thickness applied, type of texture, surface porosity, imperfections, temperature & wastage during painting.

Depends on thickness applied but generally 1– 2½ m²/kg.

Surface preparation & Application:

Surface	Preparation	Application
Floor screed	Ensure that the surface is clean, dry and free from dust and grease before application commences.	Apply a liberal coat of the adhesive on the surfaces to be bonded using a comb trowel. Do not cover too large an area at any one time. Allow drying for approximately 1 minute. Place the blocks (surfaces to be joined) in position with firm but not excessive pressure.

Availability: From Crown Depots in Nairobi, Kisumu, Mombasa, Meru, Nyeri, Eldoret, Arusha, Mwanza, Dar es Salaam, Kigali and through Crown Stockists.

Storage Conditions: Store under cool dry conditions away from direct sunlight, heat and extreme cold.

TECHNICAL DATA SHEET



If you like it... Crown it!

Disclaimer: The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Crown Paints Kenya PLC control.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Crown Paints Kenya PLC reserves the right to amend the TDS without any further notice.

It is the responsibility of the user to ensure that the latest TDS is being used for reference.



For additional health & safety information, please refer to our Material Safety Data Sheet (MSDS)