

Crown 2502 Stronghold Wood Adhesive

PRODUCT DESCRIPTION

Type: A homopolymer based wood adhesive.

Recommended use: Jointing and bonding of timber and plywood.

Substrates: Wood, chipboard, block board, veneers decorative laminates and other similar substrates.

Advantages: High bonding power. Quick drying. Water based - environmentally friendly/easy clean up. Low timber staining characteristics

PRODUCT DATA:

Colour Range: White viscous liquid

Pack Sizes: ½ Kg, 1Kg, 4Kg and 20Kg

Thinner & equipment cleaner: Water

Thinning: Supplied ready for use. DO NOT THIN

Drying Times: Hard Dry 1-2 hours **Full Cure:** 4 - 8 hours

APPLICATION DATA:

The product can be applied by: Brush

Spreading Capacity per coat: Depends on film thickness applied, type of texture, surface porosity, imperfections, temperature & wastage during painting.

Depends on thickness applied but generally 1– 3 m²/kg.

Surface preparation & Application:

Surface	Preparation	Application
Wood or boards	Moisture content of timber should be <15 %. Joints should be smooth and well fitted. The surfaces to be bonded must be close fitting and free from dirt, grease or any other contamination that may interfere with the adhesion. Abrading the surface of the joint before assembling is recommended	Apply a liberal coat of the adhesive (2-3mm thick) with a clean brush to both surfaces to be bonded. Do not cover too large an area at any one time. Allow to dry for approximately 2-3 minutes. Bring both surfaces together. On completing the joint, hold or clamp with a firm but not excessive pressure. A damp cloth can be used to remove excess wet adhesive. Allow to fully set for a period of 4 – 8 hours before removing the pressure.

TECHNICAL DATA SHEET



Availability: From Crown Depots in Nairobi, Kisumu, Mombasa, Meru, Nyeri, Eldoret, Arusha, Mwanza, Dar es Salaam, Kigali and through Crown Stockists.

Storage Conditions: Store under cool dry conditions away from direct sunlight, heat and extreme cold.

Disclaimer: The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Crown Paints Kenya PLC control.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

Crown Paints Kenya PLC reserves the right to amend the TDS without any further notice.

It is the responsibility of the user to ensure that the latest TDS is being used for reference.



For additional health & safety information, please refer to our Material Safety Data Sheet (MSDS)